




Ersatztuch



Senkrechtmarkise



Zip



Fallarmarkise



Markisolette



Balkonumrandung



Rollo




Flächenvorhang


Textilscreens - Sergé 600



S600/002002
white



S600/002007
white/pearl grey




S600/008007
linen/pearl grey



S600/007082
grey/white sand



S600/033033
sandstone



S600/002061
white/white grey



S600/007002
pearl grey/white



S600/001002
grey/white



S600/07007
pearl grey



S600/033001
oyster shell



S600/03201
duck egg




S600/033032
soft clay



S600/008015
linen/lichen



S600/001001
grey




S600/001061
grey/white grey



S600/001010
grey/charcoal



S600/010010
charcoal



S600/010011
charcoal/bronze

SOLARMATIC's Sergé 600 % ist der ideale Sonnenschutz-Behang für Senkrecht- und Fallarmarkisen, sowie Markisoleetten.

Einsatzbereiche

- sommerlicher Wärmeschutz für Wohn- und Arbeitsräume


Gewebeeigenschaften



Ballenbreite
350 cm



Gewicht
520 g/m²




42 %
Glasfaser
58 %
PVC

Gewebe



schwer entflammbar
nach DIN 4102 B1



Öffnungsfaktor
5 %



licht- und wärmetechnische Eigenschaften als Richtwerte mit Referenzverglasung lt. DIN 14501

Stoff-Nr.	Farbe	LT	F _C -Wert
S600/002002	white	21	0,36
S600/002007	white / pearl grey	11,5	0,42
S600/008007	linen / pearl grey	10,8	0,43
S600/007082	grey / white sand	8,7	0,43
S600/033033	sandstone	7,1	0,50
S600/002061	white / white grey	12,4	0,38
S600/007002	pearl grey / white	11,7	0,40
S600/001002	grey / white	6,7	0,45
S600/007007	pearl grey	10,1	0,45

Stoff-Nr.	Farbe	LT	F _C -Wert
S600/033001	oyster shell	8,3	0,51
S600/032031	duck egg	7,1	0,50
S600/033032	soft clay	7,8	0,49
S600/008015	linen / lichen	8,3	0,50
S600/001001	grey	3,5	0,52
S600/001061	grey / white grey	3,9	0,46
S600/001010	grey / charcoal	3,6	0,54
S600/010010	charcoal	3,6	0,55
S600/0100011	charcoal / bronze	6,1	0,54

LT = Lichttransmission in % / F_C-Wert bei Referenzverglasung g = 0,59 und UG = 1,2

nach DIN 14501

Stoff-Nr.	Blendschutz- klasse	Sichtschutz bei Nacht	Sichtkontakt nach außen	Tageslicht- nutzung
S600/002002	1	2	0	2
S600/002007	0	1	3	1
S600/008007	1	2	1	1
S600/007082	1	1	3	1
S600/033033	1	1	3	1
S600/002061	1	2	1	1
S600/007002	1	2	1	1
S600/001002	3	2	2	1
S600/007007	1	1	3	1

Stoff-Nr.	Blendschutz- klasse	Sichtschutz bei Nacht	Sichtkontakt nach außen	Tageslicht- nutzung
S600/033001	1	1	3	1
S600/032031	1	1	3	1
S600/033032	1	1	3	1
S600/008015	1	2	1	1
S600/001001	3	2	2	1
S600/001061	3	2	2	1
S600/001010	3	2	2	1
S600/010010	3	2	2	1
S600/0100011	1	1	3	1

LT = Lichttransmission in % / g_{tot} bei Referenzverglasung g = 0,59 und UG = 1,2